

Jack-up Accommodation Rig



$\overline{}$						
	n	Δ	ra	٠	n	Г

JUB Pacific Pte Ltd in partnership with GPK

Class

BV, Accommodation Jack Up

	Main Particulars
Length	219 ft

Breadth 209 ft Depth 23 ft

Legs Spacing 3 x 460 ft apart, Triangular Truss

Legs Spacing Transverse 127 ft Spud Cans 43 ft x 50 ft x 24 dt

Cranage

Rig Cranes 3 x ABS Approved Model OC-

54373-3 located at

FWD/STBD/PORT, 100 ft boom, 45ft main hook reach. Pedestal stype 8st @ 30.5m @ 5m/min speed and 45 st @ 7.4m @ 5m/min; Fitted with hook indicator, Audible alarm, Automatic brake

Power Equipment

Main Power 5 x CAT D399TA (1,073HP)

Emergency Power 1 x CAT D3412 (670HP)

Power Distribution SCR System6 x Hill Graham SCR

Bridges rated @ 1,200KVA 600V, 1 x Alstom SCT Bridges rated @

1,200KVA 750V

* This vessel spec if given in good faith & assumed to be correct. Details given are without guarantee

* Owner reserved the right to amend the specification without notification

Designer Builders

Mitsui MODEC 300-C-35

Builder / Year Built / Latest Upgrade

Mitsui Engineering & Shipbuilding Co.ltd / 1981/2014-2015

Operat	ina con E	auaua.	
A TOTAL PER	1111211	25 25 4 4	21121

Water Depth 300 ft

Variable Deck Load 2.937 T (300 FWD, 70 Knots)

Air Gap

Site Specific

Survival Conditions Water Depth 300 Ft

Wind Speed 100 knots, wave height 40ft, Period 8 secs

Mooring

Winches 4x MAPE

Wire / Chain 2,000ft, 1 - 1/2" diameter
Anchors 4 x 6.8MT Moor Fast Anchors

Storage Capacities

Fuel Oil 2,440 bbls
Pre-load 29,681 bbls
Portable Water 4,233 bbls
Dirty Oil Storage 78 bbls

Jacking

Make / Type Mitsui National / Electric Motor

Jacking Speed 1.5 ft/min

Helideck

Helideck S-61, 70 ft diameter

Accomodation

Total POB up to 251 men incl. marine crew